

# 650V 27mΩ Silicon Carbide Power MOSFET


## Features

- High blocking voltage with low on-resistance
- High switching speed with low capacitance
- Very fast and robust intrinsic body diode with low reverse recovery
- Very low switching losses
- Excellent avalanche ruggedness
- RoHS compliant



## Benefits

- Greater system efficiency
- Reduced cooling requirements
- Increased power density
- Increased system switching frequency
- Easy to parallel and simple to drive



## Potential Applications

Package Type: TO-247-4L

- Solar inverters
- Uninterrupted power supplies
- Switch mode power supplies
- Motor drives



## Description

The Sanan Semiconductor 650V/27mΩ silicon carbide power MOSFET uses advanced SiC MOSFET technology with low on-resistance, low switching losses, and a high operation temperature of 175°C. It is suitable for use in high frequency circuits and provides a reduction in overall system size, increased efficiency and increased switching frequency. It has been widely used in applications including solar inverters, uninterrupted power supplies, switch mode power supplies, and motor drives. Using RoHS compliant components, it is qualified for use in industrial application.

## Product Specifications

Device	V <sub>DS</sub>	I <sub>D</sub> (25°C)	R <sub>(DS)on</sub>	Marking
SMS0650027M	650V	78A	27mΩ	MS0650027M

## CONTENTS

<b>Features</b> .....	1
<b>Benefits</b> .....	1
<b>Potential Applications</b> .....	1
<b>Description</b> .....	1
<b>Product Specifications</b> .....	1
<b>Table 1 Maximum Ratings</b> .....	3
<b>Table 2 Thermal Resistances</b> .....	3
<b>Table 3 Static Electrical Characteristics</b> .....	4
<b>Table 4 Dynamic Electrical Characteristics</b> .....	4
<b>Table 5 Switching Characteristics</b> .....	5
<b>Table 6 Reverse SiC Diode Characteristics</b> .....	6
<b>Electrical Characteristic Diagrams</b> .....	7
<b>Package Information</b> .....	15
<b>Recommended Solder Pad Layout</b> .....	16
<b>Ordering Information</b> .....	16
<b>Important Notices – Read Carefully</b> .....	17
<b>Warning</b> .....	17

## Table 1. Maximum Ratings

( $T_c = 25^\circ\text{C}$ , unless otherwise specified)

Parameter	Symbol	Value	Unit	Test conditions	
Drain-source voltage	$V_{DS\max}$	650	V	$V_{GS} = 0\text{V}$ , $I_D = 100\mu\text{A}$	
Gate-source voltage, max. transient voltage	$V_{GS\max}$	-10/+25		$t_p \leq 0.5\text{us}$ , D < 1%	
Gate-source voltage, max. static voltage	$V_{GS\max}$	-8/+22			
Gate-source voltage	$V_{GSop}$	-5/+18		Recommended operation values	
Continuous drain current	$I_D$	78	A	$V_{GS} = 18\text{V}$	
		55		$V_{GS} = 18\text{V}$ , $T_c = 100^\circ\text{C}$	
Pulsed drain current	$I_{D(\text{pulse})}$	195	A	Pulse width $t_p$ limited by $T_{j\max}$	
Power dissipation	$P_{\text{tot}}$	375	W		
Operating junction temperature	$T_j$	-55~175	°C		
Storage temperature	$T_{stg}$	-55~175	°C		
Soldering temperature	$T_L$	260	°C	1.6mm from case for 10s	
Mounting torque	M	0.7	Nm	M3 screw	

## Table 2. Thermal Resistances

Parameter	Symbol	Values			Unit	Test condition
		Min.	Typ.	Max.		
Thermal resistance from junction to case	$R_{th(j-c)}$	/	0.40	/	°C/W	
Thermal resistance from junction to ambient	$R_{th(j-a)}$	/	/	40	°C/W	

**Table 3. Static Electrical Characteristics**(T<sub>j</sub> = 25°C, unless otherwise specified)

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Drain-source breakdown voltage	V <sub>(BR)DSS</sub>	650	/	/		V <sub>GS</sub> = 0V, I <sub>D</sub> = 100µA
Gate threshold voltage	V <sub>GS(th)</sub>	1.8	2.8	4.2	V	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 10mA
		/	2.0	/		V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 10mA, T <sub>j</sub> = 175°C
Drain-source leakage current	I <sub>DSS</sub>	/	1	50	µA	V <sub>DS</sub> = 650V, V <sub>GS</sub> = 0V
Gate-source leakage current	I <sub>GSS</sub>	/	1	250	nA	V <sub>GS</sub> = 18V, V <sub>DS</sub> = 0V
Drain-source on-state resistance	R <sub>DS(on)</sub>	/	32	/	mΩ	V <sub>GS</sub> = 15V, I <sub>D</sub> = 30A
		/	27	36		V <sub>GS</sub> = 18V, I <sub>D</sub> = 30A
		/	49	/		V <sub>GS</sub> = 18V, I <sub>D</sub> = 30A, T <sub>j</sub> = 175°C
Transconductance	g <sub>fs</sub>	/	20	/	S	V <sub>DS</sub> = 20V, I <sub>D</sub> = 30A
		/	19	/		V <sub>DS</sub> = 20V, I <sub>D</sub> = 30A, T <sub>j</sub> = 175°C
Internal gate resistance	R <sub>g(int)</sub>	/	2.8	/	Ω	f = 1MHz, V <sub>AC</sub> = 25mV

**Table 4. Dynamic Electrical Characteristics**(T<sub>j</sub> = 25°C, unless otherwise specified)

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Input capacitance	C <sub>iss</sub>	/	2137	/		
Output capacitance	C <sub>oss</sub>	/	196	/	pF	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 600V, f = 1MHz, V <sub>AC</sub> = 25mV
Reverse transfer capacitance	C <sub>rss</sub>	/	11	/		
C <sub>oss</sub> stored energy	E <sub>oss</sub>	/	41	/	µJ	
Gate to source charge	Q <sub>GS</sub>	/	31	/	nC	V <sub>DD</sub> = 400V, V <sub>GS</sub> = -5/+18V, I <sub>D</sub> = 30A, I <sub>GS</sub> = 1mA
Gate to drain charge	Q <sub>GD</sub>	/	27	/		
Total gate charge	Q <sub>G</sub>	/	99	/		

## Table 5. Switching Characteristics

( $T_j = 25^\circ\text{C}$ , unless otherwise specified)

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Turn-on delay time	$t_{d(on)}$	/	12	/	ns	$V_{DD} = 400V$ , $V_{GS} = -5/+18V$ , $I_D = 30A$ , $R_{G(ext)} = 4.7\Omega$ , $L = 110\mu\text{H}$ $T_j = 25^\circ\text{C}$
Rise time	$t_r$	/	18	/		
Turn-off delay time	$t_{d(off)}$	/	36	/		
Fall time	$t_f$	/	8	/		
Turn-on switching energy	$E_{on}$	/	111	/	$\mu\text{J}$	$V_{DD} = 400V$ , $V_{GS} = -5/+18V$ , $I_D = 30A$ , $R_{G(ext)} = 4.7\Omega$ , $L = 110\mu\text{H}$ $T_j = 175^\circ\text{C}$
Turn-off switching energy	$E_{off}$	/	29	/		
Turn-on delay time	$t_{d(on)}$	/	11	/		
Rise time	$t_r$	/	18	/		
Turn-off delay time	$t_{d(off)}$	/	44	/	$\mu\text{J}$	$V_{DD} = 400V$ , $V_{GS} = -5/+18V$ , $I_D = 30A$ , $R_{G(ext)} = 4.7\Omega$ , $L = 110\mu\text{H}$ $T_j = 175^\circ\text{C}$
Fall time	$t_f$	/	9	/		
Turn-on switching energy	$E_{on}$	/	116	/		
Turn-off switching energy	$E_{off}$	/	31	/		

**Table 6. Reverse SiC Diode Characteristics**
 $(T_j = 25^\circ\text{C}, \text{unless otherwise specified})$ 

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Diode forward voltage	$V_{SD}$	/	3.8	/	V	$V_{GS} = -5\text{V}, I_{SD} = 15\text{A}$
		/	3.3	/		$V_{GS} = -5\text{V}, I_{SD} = 15\text{A}, T_j = 175^\circ\text{C}$
Continuous diode forward current	$I_S$	/	/	78	A	$V_{GS} = -5\text{V}, T_C = 25^\circ\text{C}$
Diode pulse current	$I_{S, \text{pulse}}$	/	/	195	A	$V_{GS} = -5\text{V}, \text{pulse width } t_p \text{ limited by } T_{j\max}$
Reverse recovery time	$t_{rr}$	/	19	/	ns	$V_{GS} = -5\text{V}, I_{SD} = 30\text{A}, V_R = 400\text{V}, dI_f/dt = 1.33\text{kA}/\mu\text{s}, T_j = 25^\circ\text{C}$
Reverse recovery charge	$Q_{rr}$	/	0.27	/	$\mu\text{C}$	
Peak reverse recovery current	$I_{rrm}$	/	24	/	A	
Reverse recovery time	$t_{rr}$	/	23	/	ns	$V_{GS} = -5\text{V}, I_{SD} = 30\text{A}, V_R = 400\text{V}, dI_f/dt = 1.31\text{kA}/\mu\text{s}, T_j = 175^\circ\text{C}$
Reverse recovery charge	$Q_{rr}$	/	0.41	/	$\mu\text{C}$	
Peak reverse recovery current	$I_{rrm}$	/	30	/	A	

## Electrical Characteristic Diagrams




Figure 1. Output characteristics at  $T_j = -55^\circ\text{C}$




Figure 2. Output characteristics at  $T_j = 25^\circ\text{C}$




Figure 3. Output characteristics at  $T_j = 175^\circ\text{C}$




Figure 4. Normalized on-resistance vs. temperature




Figure 5. On-resistance vs. drain current  
for various temperatures




Figure 6. On-resistance vs. temperature  
for various gate voltages




Figure 7. Transfer characteristic  
for various junction temperatures




Figure 8. Body diode characteristic at  $T_j = -55^\circ C$




Figure 9. Body diode characteristic at  $T_j = 25^\circ\text{C}$ Figure 10. Body diode characteristic at  $T_j = 175^\circ\text{C}$ 

Figure 11. Threshold voltage vs. temperature




Figure 12. Gate Charge Characteristic




Figure 13. 3rd quadrant characteristic  
 at  $T_j = -55^\circ\text{C}$




Figure 14. 3rd quadrant characteristic  
 at  $T_j = 25^\circ\text{C}$




Figure 15. 3rd quadrant characteristic  
 at  $T_j = 175^\circ\text{C}$




Figure 16. Output capacitor stored energy




Figure 17. Capacitance vs. drain-source voltage  
(0 - 200V)




Figure 18. Capacitance vs. drain-source voltage  
(0 - 600V)




Figure 19. Continuous drain current derating  
vs. temperature




Figure 20. Maximum power dissipation derating  
vs. temperature




 Figure 21. Switching Times vs.  $R_{G(\text{ext})}$ 


Figure 22. Clamped inductive Switching energy vs. drain current





Figure 23. Clamped inductive Switching energy vs. temperature


 Figure 24. Clamped inductive Switching energy vs.  $R_{G(\text{ext})}$





 Figure 25. Reverse recovery charge vs.  $di/dt$ 

 Figure 26. Reverse recovery current vs.  $di/dt$ 


Figure 27. Transient thermal impedance

(Junction - Case)




Figure 28. Safe Operating Area




Figure 29. Switching times definition





Figure 30. Clamped inductive switching waveform  
test circuit

## Package Information




Dimension unit: [mm]			
Symbol	Min	Nom	Max
A	4.80	5.00	5.20
A1	2.21	2.41	2.61
A2	1.85	2.00	2.15
b	1.11	1.21	1.36
b1	1.11	1.37	1.57
b2	2.24	2.40	2.60
b3	2.11	2.21	2.36
c	0.51	0.60	0.75
D	20.70	20.90	21.30
D1	15.92	16.22	16.52
D2	1.00	1.20	1.35
E	15.50	15.80	16.10
E1	13.00	13.30	13.60
E2	4.80	5.00	5.20
E3	2.30	2.50	2.70
e	2.54 BSC		
e1	5.08 BSC		

Dimension unit: [mm]			
Symbol	Min	Nom	Max
L	19.62	19.92	20.22
L1	-	-	4.30
ØP	3.40	3.60	3.80
ØP1	-	-	7.30
Q	5.40	5.80	6.20
S	6.20 BSC		

## Recommended Solder Pad Layout

Note: All dimensions are in mm



## Ordering Information

Part number	SMS0650027M-ISATH
Package	TO-247-4L
Unit quantity	300 EA
Packing type	Tube

## Important Notices – Read Carefully

Before you use our products, you are requested to carefully read this document and fully understand its contents. Sanan Semiconductor Co., Ltd. shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of Sanan's products.

Sanan Semiconductor Datasheets are subject to change. Information presented in this document is from the characterization of engineering lots. Sanan Semiconductor Co., Ltd reserves the right to change limits, test conditions, and dimensions without notice. Information contained in this document are typical values and shall in no event be regarded as a guarantee of characteristics. With respect to any information regarding the application of the product, Sanan hereby disclaims all warranties and liabilities of any kind. The information in this document is exclusively for trained technical staff. It is the responsibility of the customer's technical department to decide the suitability of the product in the customer's application and Sanan Semiconductor Co., Ltd assumes no responsibility or liability whatsoever for the use of the information contained in this document.

In case there is any clause in this document or in any other documents which is contradictory to this clause, this clause shall prevail. This clause shall survive after termination of this document.

## Warning

Due to technical requirements, Sanan's products may contain dangerous substances. For detailed information about the substance(s), please contact the Sanan office. Sanan Semiconductor Co., Ltd bears no responsibility for any damage whatsoever due to the substance(s) used in Sanan's products.

## Contact info

Website: <https://www.sanan-semiconductor.com/>  
<https://www.sanan-semiconductor.com/en>